

AQUA-WIZZARD



**What a Wizzard For Removing Unwanted
Water From Your Sporting Venue.
End The Drama. Ring Us Today!**

**Free Call 1800 037 075
Or Fax Us on 03 53381006**

The Mentay Aqua Wizzard Is Designed To. . .

Soak It Up!



Don't Let That sudden down pour
spoil your day -
Get a Mentay Aqua Wizzard!

Like a wave of the Magician's wand
Water will simply disappear

Remember No Sport is Played
Unless you have a Mentay Aqua Wizzard

**Ring today
and order your Mentay Aqua-Wizzard**

Or for more details ring our office on Free Call 1800 037 075
or contact our agent closest to you.

AQUA-WIZZARD



CHECK OUT THESE FEATURES:-

Fully Hydraulic jack down Power Steering -
gives you great control!

Pump -
to smoothly disperse that unwanted water

Swivel Seat -
for comfortable and ergonomic support.

Weather Cover -
for protection and clear vision even in the rain.

Mentay is always designing and refining
so pass on your comments and ideas when you next talk to us.

**What a Wizzard For Removing Unwanted
Water From Your Sporting Venue.
End The Drama. Ring Us Today!**

**Free Call 1800 037 075
Or Fax Us on 03 53381006**

MENTAYAQUA-WIZZARD

SPECIFICATIONS:

- Motive Power: Gasoline Engine Standard
- Briggs and Stratton Vanguard 18Hp Petrol 3600 RPM Minimum
- Breather Fill for Hydraulic Oil - TR2 or Equivalent
- Hydraulic Power Assisted Squeeze Roller. Ram's 150 mm x 12 mm shaft with spring return.
- Flexilock Coupling Spline 1 inch to 15 tooth.
- Suction Oil Filter - SR1
- In Line Filter - Prince FB1012-10
- Transmission (Hydrostatic) Sunstrand H2-28D with Charge Pump
- Bearings are all off the shelf components
- Drive - Hydraulic Motor - DM21 Water Pump Onga Model 122 (Approx 280L)
- Drive Motor Coupled to Main Drum Danfoss OMR 250 - (Alternative Unit Wheel Motor)
- Crossline Relief Valve
- Power Steering Cylinder & Control Valve
- 200 mm Stroke x 1.25" Ram x 1" Ball Joint Connections
- 4 Cylinder Jack Down Legs
- Braking (Automatic)
- Hydraulic Reservoir has 15 L minimum of Tellus 46 Castrol (Hyspin 46)
- Front and Rear Rollers 600 mm Diameter, Perforated and Electrogalvanised
- (Stainless Steel optional Extra) with 25 mm or 40 mm Foam

SHIPPING DIMENSIONS:

- 2550 mm Long x 2250 mm Wide x 2100 mm High with Perspex Cover.
- 1500 mm Height without cover
- Export Height 1500 mm

ABSORPTION BLANKET:

- 25 mm Thickness (Oil Resistant Optional)

ROLLER WEIGHT:

- Tare Weight 920 kg Approximately (Without Ballast).

DRUM DIMENSIONS:

- 1800 mm Wide x 600 mm Diameter
- Optional Stainless Steel Drums

For Further Information or a Demonstration of our Products Contact:

Mr. Maurice Menhennet
Mentay Steel Fab Constructions Pty Ltd
P.O. Box 172, Wendouree 3355, Vic, Australia
Phone: (03) 5339 5004/5339 1733 Toll Free 1800 037 075
Fax: (03) 5338 1006

New Zealand:

Mr. Milton Koehler
2 Innes Place, Palmerston North

New South Wales:

Turfwell Sales Pty Ltd
P.O. Box 384
Maroubra, NSW 2035

Phone: (02) 9526 1844 Mobile: (018) 263 516 Fax: (02) 9526 1843

Name:.....

Address:.....

.....Postcode:.....

Nature of Enquiry:.....

Phone Number:.....